

Printing date 02/19/2015 Reviewed on 02/09/2015

1 Identification

· Product identifier

· Trade name: SprayEZ 2000 Resin

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Spray Equipment and Coatings Inc 850709 US Hwy 17 Yulee, FL 32097

USA

sales@sprayez.com

· Information department: EH&S Department

· Emergency telephone number:

During normal operating hours: (770) 528-9556

ChemTrec: (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



STOT SE 2 H371 May cause damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

2-dimethylaminoethanol

Polyol(s)

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

May cause damage to organs.

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)



Printing date 02/19/2015 Reviewed on 02/09/2015

Trade name: SprayEZ 2000 Series Resin

(Contd. of page 1)

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

In case of inadequate ventilation wear respiratory protection.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If swallowed: Call a doctor if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

If on skin: Wash with plenty of soap and water.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



2 Health = 2Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous co	omponents:	
940912-28-7	Polyether Polyol	15-40%
	Polyol(s)	15-40%
13674-84-5	tris(2-chlorisopropyl)-phosphate	5-10%
I	1,1,1,3,3-pentafluorobutane	5-10%
108-01-0	2-dimethylaminoethanol	1-5%
	triethyl phosphate	1-5%
	diethylene glycol	1-5%
460-73-1	1,1,1,3,3-Pentafluoropropane	1.0%

(Contd. on page 3)



Printing date 02/19/2015 Reviewed on 02/09/2015

Trade name: SprayEZ 2000 Resin

(Contd. of page 2)

33329-35-0 N,N-bis[3-(dimethylamino)propyl]-N',N'-dimethylpropane-1,3-diamine

1.0%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of exposure may occur after several hours; therefore medical observation for at least 48 hours after exposure.

First Aid responders should pay attention to self-protection and use the recommended protective clothing. If potential for exposure exists refer to Section 8 for specific personal protective quipment.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Suitable emergency safety shower should be immediately available.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Immediately call a doctor.

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

· Information for doctor:

Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: Do no use direct water stream. May spread fire.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

There are no known unusual fire or expolsion hazards.

- · Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.

· Additional information

(Contd. on page 4)



Printing date 02/19/2015 Reviewed on 02/09/2015

Trade name: SprayEZ 2000 Resin

(Contd. of page 3)

Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers. Fight fire from protected location or safe distance. Move container(s) from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off if not contained, may cause environmental damage.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Isolate area. Keep unnecessary and unprotected personnel from entering the area. Spilled material may cause slipping hazard. Refer to Section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

· Environmental precautions:

Prevent from entering into soil or ditches. Inform the relevant authorities if the product has caused environmental pollution.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Contain spilled material if possible. Absorb with materials such as: Dirt, Sand, Sawdust. Collect in suitable and properly labeled containers. Wash the spill site with water. See Section 13, Disposal Considerations, for additional information.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Do not swallow. Wash thoroughly after handling. Keep container closed. See Section 8, Exposure Controls and Personal Protection.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Storage Period: 6 months

Storage Temp: 15 -35

 \cdot *Specific end use*(s) *See the technical data sheet on this product for further information.*

TICA



Printing date 02/19/2015 Reviewed on 02/09/2015

Trade name: SprayEZ 2000 Resin

(Contd. of page 4)

8 Exposure controls/personal protection

· Control parameters

· Compo	· Components with limit values that require monitoring at the workplace:			
940912	940912-28-7 Polyether Polyol			
PPM	Ceiling limit value: .3 mg/m³			
78-40-	0 triethyl phosphate			
WEEL	Long-term value: 7.45 mg/m³			
1	111-46-6 diethylene glycol			
WEEL	Long-term value: 10 mg/m³			
460-73	460-73-1 1,1,1,3,3-Pentafluoropropane			
TWA	Long-term value: 1644 mg/m³			
	300 ppm			

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure at low atmospheric levels use an approved air-purifying respiratory equiped with an organic vapor sorbent and a particle filter. In case of intensive or longer exposure use a positive pressure air-supplying respirator (air line or self-contained breathing apparatus).

· Protection of hands:



Protective gloves

The workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

· Material of gloves

Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and microorganisms. Examples of preferred glove barrier materials include: Butyl rubber, Polyethylene, EVAL, Neoprene, Nitrile, Viton. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher is recommended.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses



Tightly sealed chemical goggles consistent with EN 166 or equivalent. Wear a face-shield which allows use of chemical goggles, or wear full-face respirator to protect face and eyes when there is any likelyhood of splashes.

(Contd. on page 6)



Printing date 02/19/2015 Reviewed on 02/09/2015

Trade name: SprayEZ 2000 Resin

9 Physical and chemical properties

(Contd. of page 5)

· Body protection:

Personal protective clothing for the body should be selected based on the task being performed an the risks involved and should be approved by a specialist before handling this product.

· Information on basic physical and	chemical properties	
General Information		
· Appearance:	71	
Form: Color:	Liquid Amber colored	
Cotor: · Odor:	Amber colorea Amine-like	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
<u>*</u>	1.07 0.000	
Change in condition	Undetermined.	
Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.	
Bouing point/Bouing range:	Опаелеттіпеа.	
Flash point:	> 110 °C (> 230 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:		
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density:	Not determined.	
· Relative density	Not determined.	
Vapour density	Not determined.	

· Solubility in / Miscibility with Water:

Water: Not miscible or difficult to mix.

 $\cdot \textit{Partition coefficient (n-octanol/water):} \ \textit{Not determined}.$

· Viscosity:

· Evaporation rate

Dynamic:Not determined.Kinematic:Not determined.

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability This product is stable at recommended storage conditions (See Section 7).

Not determined.

(Contd. on page 7)



Printing date 02/19/2015 Reviewed on 02/09/2015

Trade name: SprayEZ 2000 Resin

(Contd. of page 6)

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Avoid moisture to protect product quality.
- · Incompatible materials:

Avoid contact with oxidizing materials. Avoid contact with: Strong acids. Strong bases. Avoid unitended contact with isocyanates. The reaction of polyols and isocyanates generate heat.

· Hazardous decomposition products: CO and CO2

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values that	are relevant for classification:			
940912-28	940912-28-7 Polyether Polyol				
Oral	LD50	1370 mg/kg (rat)			
Dermal	LD50	12800 mg/kg (rabbit)			
33329-35-	33329-35-0 N,N-bis[3-(dimethylamino)propyl]-N',N'-dimethylpropane-1,3-diamine				
Oral	LD50	2445 mg/kg (rat)			
Dermal	LD50	1150 mg/kg (rabbit)			
Inhalative	LC50/4 h	1.9 mg/l (rat)			

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
940912-28-7	Polyether Polyol	
88-12-0	1-vinyl-2-pyrrolidone	
,	al Toxicology Program)	
940912-28-7	Polyether Polyol	
,	Occupational Safety & Health Administration)	
	Polyether Polyol	
13674-84-5	tris(2-chlorisopropyl)-phosphate	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 8)



Printing date 02/19/2015 Reviewed on 02/09/2015

Trade name: SprayEZ 2000 Resin

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Waste Disposal: Incinerate in a licensed facility. Do not discharge into waterways or sewer systems.

Container Disposal: Steel drums must be emptied (as defined by RCRA, Section 261.7 or state regulations that may be more stringent) and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer, or an approved landfill. Drums destined for a scrap dealer or landfill must be punctured or crushed to prevent reuse.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADN, IMDG, IATA	not regulated	
UN proper shipping name DOT, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
DOT	DOT Non-Bulk: Not Regulated	
Class	not regulated	
ADN/R Class:	not regulated	
Packing group		
DOT, IMDG, IATA	not regulated	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex II o	\overline{pf}	
MARPOL73/78 and the IBC Code	Not applicable.	

- USA

(Contd. on page 9)



Printing date 02/19/2015 Reviewed on 02/09/2015

Trade name: SprayEZ 2000 Resin

(Contd. of page 8)

15 Regulatory information	
· Safety, health and environmental regulations/legislation specific for the substance or mixture	
· Clean Air Act	
None of the ingredients is listed.	
· Clean Water Act	
None of the ingredients is listed.	
· Sara	
· SARA 302/304 Extremely Hazardous Substance	
None of the ingredients is listed.	
· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
940912-28-7 Polyether Polyol	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Massachusetts Right To Know	
460-73-1 1,1,1,3,3-Pentafluoropropane	
· New Jersey Right To Know	
112-60-7 Tetraethylene glycol	
· Pennsylvania Right To Know	
112-60-7 Tetraethylene glycol	
· Proposition 65	
· Chemicals known to cause cancer:	
940912-28-7 Polyether Polyol	
13674-84-5 tris(2-chlorisopropyl)-phosphate	
460-73-1 1,1,1,3,3-Pentafluoropropane	
· Chemicals known to cause reproductive toxicity for females:	
940912-28-7 Polyether Polyol	
13674-84-5 tris(2-chlorisopropyl)-phosphate	
Chemicals known to cause reproductive toxicity for males:	
940912-28-7 Polyether Polyol	
13674-84-5 tris(2-chlorisopropyl)-phosphate	
Chemicals known to cause developmental toxicity:	
940912-28-7 Polyether Polyol	
13674-84-5 tris(2-chlorisopropyl)-phosphate	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· TLV (Threshold Limit Value established by ACGIH)	
88-12-0 1-vinyl-2-pyrrolidone	A3
1	ntd. on page 10)



Printing date 02/19/2015 Reviewed on 02/09/2015

Trade name: SprayEZ 2000 Resin

(Contd. of page 9)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

2-dimethylaminoethanol

Polyol(s)

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

May cause damage to organs.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

In case of inadequate ventilation wear respiratory protection.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If swallowed: Call a doctor if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

If on skin: Wash with plenty of soap and water.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Spray Equipment and Coatings urges each customer of recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown on this (M)SDS. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his/her activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M) SDS, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you

(Contd. on page 11)



Printing date 02/19/2015 Reviewed on 02/09/2015

Trade name: SprayEZ 2000 Resin

(Contd. of page 10)

have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most curent version.

- · Recommended restriction of use FOR PROFESSIONAL USE ONLY
- · Department issuing SDS: Environmental Health & Safety Department.
- · Contact: M. Phillips
- · Date of preparation / last revision 02/19/2015 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2